

Foaming Agents

Polyurethane / n-Pentane



n-Pentane: Agente hinchante para EPS, XPS y Poliuretano

En-Pentane : Foaming agent for EPS, XPS and Polyurethane

n-pentane is a liquid hydrocarbon obtained from petroleum that is mainly used for the manufacture of rigid polyurethane, but can also be used in EPS and XPS. It is characterized by having an intermediate boiling point between the pentanes used in the insulation industry.

When used in polyurethane, foams with lower density, good dimensional stability, and mechanical properties are obtained, which is why it is usually used in the manufacture of continuous polyurethane panels.

Chemical Name:

Normal-pentane

CAS Number:

109-66-0



Technical Characteristics:

- > Extremely flammable and colorless liquid hydrocarbon.
- > Good chemical stability.
- > Lower thermal conductivity than other pentanes used in PU.
- > Does not affect the ozone layer and low global warming potential (GWP).
- > Product with high impact in terms of SEVESO regulation due to its high flammability and low boiling point.

Packaging:

- Drums
- Roll drums
- Containers - Tank

Applications:



Polyurethane mainly for the manufacture of sandwich panel or mixed with other hydrocarbons.



EPS



XPS

Properties:

Chemical Formula	C5H12	
Molecular Weight	72,15	g/mol
Boiling Point	35	°C
Vapor pressure (20°C)	0,6	bara
Vapor pressure (50°C)	1,6	bara
Liquid Density (20°C)	0,63	kg/l
Liquid Density (50°C)	0,59	kg/l
Thermal conductivity (20°C)	14	mW/mK
LEL (Lower Explosive Limit)	1,4	% volume
UEL (Upper Explosive Limit)	7,8	% volume

More information:

If you want more information about our products, contact us.

EUROPE

GRIT, Gases Research Innovation & Technology

BARCELONA

Our plant:

P. I. "El Punsic", parcela 8.3,
08279 Avinyó, Barcelona. Spain.

Our office:

C/ Consell de Cent 419, Pral 1^a y 2^a,
08009, Barcelona. Spain.

Phone: (+34) 932 721 400
E-mail: grit@grit.es
Website: www.gasesgrit.com

USA

Summit Refrigerants

HOUSTON

8541 East North Belt
Humble, Texas 77396

Phone: (+1) 281-540-2653
Toll-Free: (+1) 866-971-2653
Fax: (+1) 281-540-0385

DALLAS

2080 McDaniel Drive
Suite 200
Carrollton, Texas 75006

Phone: (+1) 469-458-3195
Fax: (+1) 469-458-3085

BATON ROUGE

10080 Industriplex Avenue
Gonzales, LA 70737

Phone: (+1) 225-744-2653
Fax: (+1) 225-677-6106